

LI-ION RECHARGEABLE

VIRIBUS™ INTRINSICALLY SAFE DUAL-LIGHT LANTERN

XPR-5580R  
XPR-5580G

**NIGHTSTICK**®  
Life Depends on Light™



**Rear green safety lights** provide visibility in smoke filled applications. Includes one Li-ion battery (expandable to 3).



**Carry strap with seat belt style buckle** for additional hands-free use and safety.



**Convenient locking snap-in charger** included.



Sealed switches and body for **dustproof/waterproof (IP-67)** rating, as well as chemical/heat resistant for any environment.

**DUAL LIGHT TECHNOLOGY**



# 300 LUMENS DUAL-LIGHT

HIGH, MEDIUM & LOW SPOTLIGHT  
HIGH, MEDIUM & LOW FLOODLIGHT

**ZONE 0**

**CLASS I DIV 1**

**IT FLOATS**



AVAILABLE IN MULTIPLE COLORS.



FL1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	210 LUMENS	30 LUMENS	300 LUMENS
	12h	65h	9h 15min
	635m		
	101000cd		
	2m		
	1m		

**210 LUMENS**

1-800-233-2155 · 1-469-326-9400 · [nightstick.com](http://nightstick.com)

© 2022 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

**VIRIBUS™**

# DUAL-LIGHT LANTERN

## LI-ION RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5580G, UPC# 017398805957  
XPR-5580R, UPC# 017398805964

### MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

### CERTIFICATIONS

- cULus, ATEX, IECEx, CE, UKCA, Meets requirements of NFPA-1971-8.6 (2016), Charger meets requirements of NFPA-1901 (2013) Mounted in any Position

### CASE MATERIAL

- Engineered polymer

### LUMENS/RUNTIME

#### FLASHLIGHT

- HIGH: 210L, 12.5 hrs. runtime
- MEDIUM: 100L, 19.5 hrs. runtime
- LOW: 30L, 65 hrs. runtime

#### FLOODLIGHT

- HIGH: 200L, 14 hrs. runtime
- MEDIUM: 100L, 19 hrs. runtime
- LOW: 30L, 65 hrs. runtime

#### DUAL-LIGHT

- 300L, 9.25 hrs. runtime

### CANDELA

#### FLASHLIGHT

- HIGH: 101,000
- MEDIUM: 16,515
- LOW: 6,705

### BEAM DISTANCE

#### FLASHLIGHT

- HIGH: 635m
- MEDIUM: 257m
- LOW: 164m

### WATER RATING

- IP-67 (dustproof and waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 8.25 in (210mm)
- WIDTH: 3.6 in (91mm)
- DEPTH: 5.5 in (140mm)
- BEZEL DIAMETER: 4.7 in (118mm)
- WEIGHT: 2 lbs. 1oz. / 936 g

### BATTERY

- Rechargeable Li-ion battery pack

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Lantern
- (1) Li-ion rechargeable battery (5500-BATT)
- Locking snap-in charger (5580-CHGR2)
- AC & DC power supply (NS-ACCORD & NS-DCCORD)
- Removable shoulder strap
- Instruction manual

FL1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	210 LUMENS	30 LUMENS	300 LUMENS
	12h	65h	9h 15min
	635m		
	101000cd		
			
			



E 467756  
ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

CE 2575

SEE INSTRUCTION MANUAL  
VOIR MANUEL

Bayco Products, Inc. XPR-5580  
Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

UL listed for use with Bayco Li-ion Battery Pack 5500-BATT

CLASS I DIV 1 GRPS A-D T4

CLASS II & III DIV 1 GRPS E-G

CLASS I ZONE 0 GRP IIC T4

CLASS II ZONE 20 IIC T135°C

© II 1 G Ex ia IIC T4 Ga

Ex ia IIC T4 Ga

DEMKO 16 ATEX 1796

UL220KEX2427

IECEA UL 16.0154

-20°C ≤ Tamb ≤ +40°C

3.7V/Cell 5500-BATT

U<sub>n</sub> = 4.75V

MFG MM-YY

### CERTIFIED

